

TREKKER MOUNTAIN

Art. No. 602007



CE EN ISO 20345:2011 S3 HRO HI CI WR SRC

Leather thickness 2.6 – 2.8 mm, cut protection level 1, waterproof and breathable with GORE-TEX® Performance, leg height 18 cm, antistatic, sole 02

Available sizes EU 36 – 47, Extra large sizes EU 48 – 49



HAIX® Climate System



HAIX® FP System



HAIX® MSL System



RTC with countersunk seams



602007

Upper Material

Oiled nubuk leather, hydrophobic, breathable (4,0 mg/cm²/h), 2.6 – 2.8 mm thick

Cut Protection

Protection against cuts certified with cut level 1 (20m/sec.). Compliant with EN ISO 17249:2013

Inner lining

GORE-TEX® Performance: 4-layer GORE-TEX® laminate, waterproof and breathable. Highly abrasion-resistant lining with fleece midlayer. Optimized- climate comfort for all year seasons and excessive use. Increased chemical protection.

Plastic Insole

Dimensionally stable, torsion-proof, avoids punctual pressure (e.g. of stones)

Foot bed

Anatomically formed, exchangeable, washable, very good moisture absorption, dries quickly

Protective Toe Cap

Anatomically formed and well-padded protective toe cap

Protective Throughsole

Flexible protective throughsole

Sole

Rubber/PU walking sole with proven street/ terrain tread, wear resistant and non-slip traction; large, bevelled contact surface and superior bending comfort. This rubber shell sole features the MSL (micro-soft-light) system that is the result of an additional production process to achieve extremely low weight, excellent cold/heat insulation, oil and gasoline resistance and non-marking characteristics. Compliant with EN ISO 20345:2011.

HAIX® Climate System

The HAIX Climate system uses the pumping movement, which permits air circulation with every step – moist air is released and fresh air comes in through the vent holes at the top of the boot.

HAIX® MSL System

MicroSoftLight: Improved damping, extremely low weight due to the PU foam across the entire sole area, good cold/heat insulation.

Others

Integrated heel bend, lacing system with eyelets permitting smooth movement, clamps and self-closed hooks, rubber toe cap, no side seams

| | | | | | | | | | | | | | | | | | | | | | | | | | |
|----|----|----|----|----|----|----|----|----|----|----|----|----|----|-----|----|-----|----|-----|----|-----|----|-----|----|-----|----|
| UK | 3 | 3½ | 4 | 4½ | 5 | 5½ | 6 | 6½ | 7 | 7½ | 8 | 8½ | 9 | 9½ | 10 | 10½ | 11 | 11½ | 12 | 12½ | 13 | 13½ | 14 | 14½ | 15 |
| EU | 35 | 36 | 37 | 37 | 38 | 39 | 39 | 40 | 41 | 41 | 42 | 43 | 43 | 44 | 45 | 45 | 46 | 47 | 47 | 48 | 48 | 49 | 50 | 50 | 51 |
| US | 4 | 4½ | 5 | 5½ | 6 | 6½ | 7 | 7½ | 8 | 8½ | 9 | 9½ | 10 | 10½ | 11 | 11½ | 12 | 12½ | 13 | 13½ | 14 | 14½ | 15 | 15½ | 16 |

HAIX®-Schuhe, Produktions- und Vertriebs GmbH

Auhofstrasse 10, 84048 Mainburg, Germany
T. +49(0)8751/8625-0, F. +49(0)8751/8625-25
info@haix.de, www.haix.com